



FREE TILE

category: antistatic vinyl composition tile

FREE TILE is a VCT with antistatic property. Suitable for industrial projects such as an electronic device factory.

Specification	overall thickness	2.0mm	size	(1) 454mm×454mm (2) 505mm×505mm (for free access floor)
Packing	(1) 454mm×454mm size: 20pcs/box = 4.12m ² /box (2) 505mm×505mm size: 20pcs/box = 5.10m ² /box			
Net Weight	(1) 454mm×454mm size: 16.1kg/box (2) 505mm×505mm size: 20.4kg/box			
Recommended Applications	factories (semiconductor or electronic devices) / offices			
Recommended Adhesive from TOLI	dried mortar and concrete	Epo Gray ST, US Cement		
	humid mortar and concrete	Epo Gray ST, US Cement		
Notes on Installation	<ul style="list-style-type: none"> ◆Before installation, make sure the arrow marks on the back of each tile, which show the direction of the pattern. ◆For one week after installation, direct sunlight, sudden change of temperature due to air conditioning, and water washing should be avoided. 			
Recommended Maintenance Wax from TOLI	"ELEX" from C×S Corporation (Antistatic)			
Custom Order	If you ask for a different size or thickness, please contact TOLI sales rep.			
Others	<ul style="list-style-type: none"> ◆505mm×505mm size is for free access floor with the surface material integrated. When you install directly on the sub-floor, please choose 454mm×454mm size. ◆The dirt and stains will be more visible on the floor covering with lighter plain colors, compared to dark colors. Also they are more likely to stick with the deep-embossed surface than the flat surface. ◆Please be aware that some rubber casters might cause color-contamination. ◆FREE TILE cannot be used for the free access floor with the surface material separated. ◆Please bear in mind that the antistatic performance might differ according to the kind of sub-floor. ◆Please note that the product has the indigenous odor from its materials. 			

Specialty Flooring

MADE IN JAPAN



TT45413 (454mm)
TT50513 (505mm)



TT45417 (454mm)
TT50517 (505mm)



TT45425 (454mm)
TT50525 (505mm)



TT45413



TT45426 (454mm)
TT50526 (505mm)



TT45427 (454mm)
TT50527 (505mm)




TT45428 (454mm)
TT50528 (505mm)



TT45439 (454mm)
TT50539 (505mm)



TT45440 (454mm)
TT50540 (505mm)



TT45441 (454mm)
TT50541 (505mm)



▲ TT50527

◆ Antistatic Property <in accordance with JIS A 1454>

	Surface (Ω)	Volume (Ω)
2.0mm vinyl composition tile	2.0×10 ¹²	1.0×10 ¹¹
FREE TILE	2.2×10 ¹⁰	1.2×10 ⁸

◆ Antistatic Property to Human Bodies <in accordance with JIS L 1021-16>

	Rubber Shoes (kV)
2.0mm vinyl composition tile	over 3.0
FREE TILE	0.6

☆ This is the test result at 23 degrees centigrade, 25%RH. Please bear in mind that antistatic property may differ due to the sub-floor.



FREE TILE S

category: antistatic solid vinyl tile

FREE TILE S is a solid vinyl tile with antistatic property. Suitable for industrial projects such as an electronic device factory.

Specification	overall thickness	2.0mm	size	454mm×454mm
Packing	20pcs/box = 4.12m ² /box			
Net Weight	17.0kg/box			
Recommended Applications	factories (electronic devices) / offices			
Recommended Adhesive from TOLI	dried mortar and concrete	Epo Gray ST		
	humid mortar and concrete	Epo Gray ST		
Notes on Installation	<ul style="list-style-type: none"> ◆Before installation, make sure the arrow marks on the back of each tile, which show the direction of the pattern. ◆For one week after installation, direct sunlight, sudden change of temperature due to air conditioning, and water washing should be avoided. 			
Recommended Maintenance Wax from TOLI	"ELEX" from C×S Corporation (Antistatic)			
Custom Order	If you ask for a different size, please contact TOLI sales rep.			
Others	<ul style="list-style-type: none"> ◆454mm×454mm size is for free access floor with the surface material integrated. When you install directly on the sub-floor, please choose 300mm×300mm size or 450mm×450mm size (on a custom basis). ◆The dirt and stains will be more visible on the floor covering with lighter plain colors, compared to dark colors. Also they are more likely to stick with the deep-embossed surface than the flat surface. ◆Please be aware that some rubber casters might cause color-contamination. ◆FREE TILE cannot be used for the free access floor with the surface material separated. ◆Please bear in mind that the antistatic performance might differ according to the kind of sub-floor. ◆Please note that the product has the indigenous odor from its materials. 			

MADE IN JAPAN



TT4545519



TT4545504



TT4545519



TT4545522



TT4545526




TT4545529




TT4545543

◆ FREE TILE S is using high-purity vinyl. Its very fine surface can prevent the dusts caused by abrasion.



2.0mm vinyl composition tile



FREE TILE S

◆ Antistatic Property <in accordance with JIS A 1454>

	Surface (Ω)	Volume (Ω)
2.0mm vinyl composition tile	2.0×10 ¹²	1.0×10 ¹¹
FREE TILE S	4.8×10 ⁸	3.3×10 ⁸

◆ Antistatic Property to Human Bodies <in accordance with JIS L 1021-16>

	Rubber Shoes (kV)
2.0mm vinyl composition tile	over 3.0
FREE TILE S	0.1

☆ This is the test result at 23 degrees centigrade, 25%RH. Please bear in mind that antistatic property may differ due to the sub-floor.