



MOKURIN

category: vinyl composition tile

MOKURIN is a wood-look VCT in plank form with natural gradation.

Specification	overall thickness	3.0mm	size	100mm×900mm
	others	Beveled		
Packing	30pcs/box = 2.70m ² /box			
Net Weight	16.1kg/box			
Recommended Adhesive from TOLI	dried mortar and concrete	Eco AR600		
	humid mortar and concrete	Epo Gray ST, US Cement, US Cement (less-smelly), US200		
Notes on Installation	<ul style="list-style-type: none"> For one week after installation, direct sunlight, sudden change of temperature due to air conditioning, and water washing should be avoided. The color shading differs on a tile-by-tile basis, which will make the floor look very natural when the tiles are installed. 			
Recommended Maintenance Wax from TOLI	New FB Wax, U Wax, T Wax (Non-shiny & Antibacterial)			
Others	<ul style="list-style-type: none"> The dirt and stains will be more visible on the floor covering with lighter plain colors, compared to dark colors. Also they are more likely to stick with the deep-embossed surface than the flat surface. Please be aware that some rubber casters might cause color-contamination. Beveled part sometimes gets bleached. This will be recovered by applying the wax. Please note that the product has the indigenous odor from its materials. 			

MADE IN JAPAN



"Vinyl Soil" (artificial soil in TOLI's product design concept) is a flexible material to describe natural textures. Just like you freely paint a picture, any color and texture can be portrayed by "Vinyl Soil".



MOT2001



MOT2002



MOT2003



MOT2008



MOT2010



MOT2011



MOT2012



MOT2013



MOT2015



MOT2016



MOT2017



MOT2018



MOKURIN MASAME (STRAIGHT GRAIN)

category: vinyl composition tile

MOKURIN MASAME is another wood-look VCT plank with a straight grain image. Its delicate warm modern colors will create a calm atmosphere.

Specification	overall thickness	3.0mm	size	150mm×900mm
	others	Beveled		
Packing	20pcs/box = 2.70m ² /box			
Net Weight	16.4kg/box			
Recommended Adhesive from TOLI	dried mortar and concrete	Eco AR600		
	humid mortar and concrete	Epo Gray ST, US Cement, US Cement (less-smelly), US200		
Notes on Installation	<ul style="list-style-type: none"> ◆For one week after installation, direct sunlight, sudden change of temperature due to air conditioning, and water washing should be avoided. ◆The color shading differs on a tile-by-tile basis, which will make the floor look very natural when the tiles are installed. 			
Recommended Maintenance Wax from TOLI	New FB Wax, U Wax, T Wax (Non-shiny & Antibacterial)			
Others	<ul style="list-style-type: none"> ◆The dirt and stains will be more visible on the floor covering with lighter plain colors, compared to dark colors. Also they are more likely to stick with the deep-embossed surface than the flat surface. ◆Please be aware that some rubber casters might cause color-contamination. ◆Beveled part sometimes gets bleached. This will be recovered by applying the wax. ◆Please note that the product has the indigenous odor from its materials. 			

MADE IN JAPAN

Vinyl Tile



"Vinyl Soil" (artificial soil in TOLI's product design concept) is a flexible material to describe natural textures. Just like you freely paint a picture, any color and texture can be portrayed by "Vinyl Soil".



MOT3501



MOT3501



MOT3502



MOT3503



MOT3505



MOT3506



MOT3507



MOT3508



MOT3509



MOT3513



MOT3514



MOT3515



MOT3516



MOT3517



MOT3518